

P-5100

THE NON-WOVEN POLYURETHANE TAPE

PRODUCT DESIGN

Conveying side	Surface	ground
	Colour	■ Gelb
Running side		
	Colour	■ Gelb
	Surface	ground
Execution	Dotted and spotted	

DIMENSIONS

Length	150 - 4000 mm
Tolerance	±2,0% (min. ±5 mm)
Width	3 - 450 mm
Tolerance	5 - 50 mm ±0,5 mm
Thickness	0,9 mm (max. 10 mm)
Tolerance	± 0,05 mm



APPLICATION

- Fabricless, elastic drive and conveyor belt
- Suitable for fixed centre distances, e.g. on dynamic weighing units
- Coating material for timing belts

CHARACTERISTICS*

Tensile strength per 10 mm endless width	220 N/cm
Recommended preload	4 – 8 %
Smallest pulley-Ø	8 mm
Antistatic	ja
Temperature resistance	-10 to +70 °C short-term +80 °C
Beschreibung Freifeld 1	This ribbon is super fun and versatile.
Beschreibung Freifeld 2	We would also like to inform you about this volume....

* based on standard version with minimum thickness

All details in our product information correspond to the current state of the art. BGK products are continuously developed and improved. Changes are therefore possible at any time. However, given the high variance in the framework conditions in practical use in the respective application, these values are not an assurance of a specific property or a guarantee.

This also applies to instructions for use, which can only represent a recommendation.